## TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701

Phone: (775) 885-9959 Fax: (775) 885-9972

## CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-9000 LDI DC	Lot# 1 (10487	Mfg. Date: ( ( - 0 Warranty Ends: 5	14-21 5-04-22
PROPERTY VISCOSITY	TEST METHOD  Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION  Before mixing: Report Only After mixing: 140 - 200 ps	RESULT 243 ps 183 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only	1.3
FINENESS OF GRIND	TA1-0-0002	5 microns maximum	5 microns
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed 🗹
FLEXIBILITY (*)	TAI-0-0025	No cracking	Passed 🗹
ADHESION (*)	TA1-0-0021	100/100 on copper	Passed I

(\*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

e, Title, Date