TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with the manufacturing specifications for this product.

S-200Y NP (USA)

Lot # 9092337

Mfg. Date: 9-23-19 Warranty Ends: 3-23-20

1/12/12

PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer	MANUFACTURING SPECIFICATION Before mixing: 290 - 350 ps	<u>RESULT</u> 276 ps 473 ps
THIXOTROPIC INDEX	5 rpms @ 25°C Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only Before mixing: 1.4 - 2.2 After mixing: Report Only	473 ps 2.0 3.1
FINENESS OF GRIND	TAI-0-0002	17.5 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination: 1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed [V]
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed 🔽
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 2 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed
SOLVENT RESISTANCE (*)	Immersion in PM Acetate 20°C / 30 mins.	No swelling, softening, or blistering	Passed
PENCIL HARDNESS (*)	TAI-0-0020	7H or greater	8 H .
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed
	EXTENSION	(284°F) in a convection over	n
retested b America C Control de and has b	-	A. P.C. SUPERVISOR	9/30/19 Date

a warranty extension.

Warranty period ends: 05/23/20

Authorized By: Luis Marquez QC Supervisor

FRM-0-0083