TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-4000 CC100SGHF	Lot#1042117	Mfg. Date: $H - 21 - 2$ Warranty Ends: $10 - 2$	-1 .1-21
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: 350 - 450 ps After mixing: 130 - 170 ps	RESULT 355 ps 165 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	Before mixing: 1.40 - 1.80 After mixing: 1.20 - 1.60	1.71
FINENESS OF GRIND	TAI-0-0002	17.5 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination: 1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed [7]
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹
TACK-DRY	Hot air convection oven 80°C / 30 minutes	Tack-free to the touch	Passed 🛂
IMAGING	ORC HMW 680GW - 7 kW 300 mJ / cm ²	Report Only (clear on copper)	11
	Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi		
RESISTANCE TO	260°C (500°F) / 30 sec x 1 cycle	No discoloration, peeling,	Passed 💟
SOLDERING (*)	Rosin-based flux	or blistering	814
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater	,
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed 🗹 ·

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By:

Ve

FRM-0-0163

5/04/09