TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-4000 SG100HF	Lot#1111847	Mfg. Date: 11-18-2- Warranty Ends: 5-18	- 22
PROPERTY VISCOSITY THIXOTROPIC INDEX	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C Toki Sangyo RE100U Viscometer	MANUFACTURING SPECIFICATION Before mixing: 420 - 520 ps After mixing: 160 - 200 ps	RESULT 434 ps 194 ps
FINENESS OF GRIND	Viscosity ratio: 5 rpm / 50 rpm TAI-0-0002	After mixing: 1.2 - 1.6	1.3 5 microns
VISUAL EXAMINATION		17.5 Incress maximum	
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed
	Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗸
TACK-DRY	Hot air convection oven 80°C / 30 minutes	Tack-free to the touch	Passed 🗗
IMAGING	ORC HMW 680GW - 7 kW 200 mJ / cm ² Horizontal Developer - 1% Na2CO3	Report Only (clear on copper)	9
DEGLOS ANON TO	30°C (86°F) / 60 secs., 28 psi		
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 30 sec x 1 cycle Rosin-based flux	No discoloration, peeling, or blistering	Passed 📝
SOLVENT RESISTANCE (*)	Immersion in PM Acetate 20°C / 20 mins.	No swelling, softening, or blistering	Passed [7]
PENCIL HARDNESS (*)	TAI-0-0020	7H or greater	8 H .
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed [4]

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By:

Verified By:

Title,

Date

FRM-0-0166

6/02/09