TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-9000 LDI DC	Lot# 911 0837	Mfg. Date:	-19-20
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: Report Only After mixing: 140 - 200 ps	RESULT 225 ps 161 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only	1, 2
FINENESS OF GRIND	TAI-0-0002	5 microns maximum	5 microns
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed 🗹
FLEXIBILITY (*)	TAI-0-0025	No cracking	Passed 🗹
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed [

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By:

d. C. Supervisor 11/21/19
Title, Date