TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-4000 H855	Lot# 9092037	Mgf. Date: 9-20-19 Warranty Ends: 3-20-	20	
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: 160 – 200 ps After mixing: 105 - 135 ps	RESUL 180 125	ps ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	Before mixing: 1.0 - 1.4 After mixing: 1.0 - 1.4	1.1	
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5 m	icrons
VISUAL EXAMINATION	Microscopic examination: 1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed	
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed,	W.
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed [*]	W
TACK-DRY	Hot air convection oven 90°C / 35 minutes	Tack-free to the touch	Passed	
IMAGING	ORC HMW 680GW - 7 kW 150 mJ / cm ² (Under Artwork)	Stouffer 21 step: 8 - 10 (clear on copper)	9	
	Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi		* 1	
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 30 sec x 1 cycle Rosin-based flux	No discoloration, peeling, or blistering	Passed	P
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed	4
RESISTANCE (*)	20°C / 20 mins.	or blistering	814	
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater	0.,	/
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed	U

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By	n. Supern	isor 9/25/19
Name,	Title,	Date