TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: S-222NA).

S-222NA (402-LV)	Lot# 100417	Mfg. Date: 10-0 リー み Warranty Ends: リー0リー	1 22	
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C		<u>RESU</u> 6,700 0,200	LT cps cps
	Brookfield DV-II Viscometer 10 rpms @ RT, spindle #6, 5 mins.	After mixing: 47,000 - 57,000 cps	51,10	o cps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only	1.9	
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5	microns
VISUAL EXAMINATION	Microscopic examination:			
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed	P
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed	V
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed	ď
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed	¥
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed	凹
RESISTANCE (*)	20°C / 30 mins.	or blistering	84	
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater		•
ADHESION (*)	TAI-0-0021	100/1 00 on copper	Passed	

(*) - Final cure for these tests was 20 minutes @ 140°C (284°F) in a convection oven

Verified By:

##- Q.C. Sulskulson 10/8/21

Name, Title, Date

FRM-0-0042