TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-9000AC).

Mfg. Date: 11-22-21 Lot# 111 2217 PSR-9000 FXT AMBER Warranty Ends: 8-22-22 MANUFACTURING TEST METHOD **SPECIFICATION** VISCOSITY Toki Sangyo RE100U Viscometer Before mixing: 180 - 220 ps 5 rpms @ 25°C After mixing: 140 - 180 ps 180 ps FINENESS OF GRIND microns TAI-0-0002 15 microns maximum VISUAL EXAMINATION Microscopic examination: Passed 1. 1-mil drawdown of wet film No bubbles, pits, voids, particles, color differences. 2. Wet film drawdown on **Passed** No bubbles, pits, voids, grind gauge particles, color differences. **RESISTANCE TO** 260°C (500°F) / 10 sec x 1 cycle **Passed** No discoloration, peeling, **SOLDERING** (*) Rosin-based flux or blistering FLEXIBILITY (*) Passed TAI-0-0025 No cracking ADHESION (*) TAI-0-0021 Passed 100/100 on copper

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

WARRANTY EXTENSION This product has been retested by the Taiyo America Quality Control department and has been granted a warranty extension.

Warranty period ends:

09/22/22

Authorized By:

Luis Marquez QC Supervisor

FRM1-0-0114

Title. Date

3/09/12