TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with the manufacturing specifications for this product.

Mfg. Date: 11.17.20
Warranty Ends: 05.17.2 Lot # 011174.7 **TER-20 K27 MANUFACTURING**

PROPERTY	TEST METHOD SPECIFICATION		RESULT	
VISCOSITY	Toki Sangyo RE100U Viscometer	<u>STEGRITATION</u>	<u>ICCOCCI</u>	
	5 rpms @ 25°C	135 - 165 ps	137 ps	3
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	1.10 – 1.50	1.48	
FINENESS OF GRIND	TAI-0-0002	, 15 microns maximum	5 micr	rons
VISUAL EXAMINATION	Microscopic examination:			
e**	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed	7
	Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed [7
SCREENABILITY	Visual inspection of screen Printed panel	No surface defects,	Passed [v	7
TACK-DRY	Hot air convection oven 90°C / 30 minutes	Tack-free to the touch	Passed	7
IMAGING	ORC HMW 680GW 7kW 100 mJ/cm ²	Stouffer step: Report Only (clear on copper)	4	
	Horizontal Developer – 1% Na2CO3 30°C (86°F) / 60 secs., 20 psi			
PENCIL HARDNESS	TAI-0-0020	H Minimum	ZH	
ADHESION	TAI-0-0021	100/100 on copper	Passed	7
STRIPPABILITY	TAI-0-0028	No ink residue	Passed [7

Verified By:

PETEBINZEL QUMANAGER
Title. Date

Name,