TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-4000 CR01MW	Lot#0120417	Mfg. Date: 12-04-5 Warranty Ends: 6-0せ	21
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer	MANUFACTURING SPECIFICATION	RESULT
	5 rpms @ 25°C	After mixing: 150 - 200 ps	186 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: 1.00 - 1.50	1.27
FINENESS OF GRIND	TAI-0-0002	15 Microns or less.	5 microns
VISUAL EXAMINATION	Microscopic examination:		
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed ø
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed U
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed 4
TACK-DRY	Hot air convection oven	Tack-free to the touch	Passed 🔽
IMAGING	ORC HMW 680GW - 7 kW 600 mJ / cm ²	Stouffer 21 step: Report Only (clear on copper)	10
	Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 -32 psi.		
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed 🗹
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed []
RESISTANCE (*)	20°C/30 mins.	or blistering	6 H ·
PENCIL HARDNESS (*)	TA1-0-0020	4H or greater	
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed
(*) - Final cure for " C (302°F) in a convection oven WARRANTY EXTENSION			
This rete Am Cor and	s product has been ested by the Taiyo erica Quality atrol department has been granted arranty extension.	Verified By: A.C. Sulervice Name, Title,	Date
FRM-0-0280 War	ranty period ends: 08/04/21 rized By:		09/25/19

Luis Marquez QC Supervisor