## TAIYO AMERICA, INC.

## 2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

## CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-4000 LDI EU

Lot # | | | 05 87 Mfg. Date: | 1 - 05 - 2 | Warranty Ends: 5 - 05 - 22

PROPERTY VISCOSITY  THIXOTROPIC INDEX FINENESS OF GRIND	TEST METHOD  Toki Sangyo RE100U Viscometer 5 rpms @ 25°C  Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm  TAI-0-0002	MANUFACTURING SPECIFICATION  Before mixing: Report Only After mixing: 180 - 220 ps  After mixing: Report Only 5 microns maximum	RESULT 463 ps 217 ps 1.3 5 microns	S
VISUAL EXAMINATION	Microscopic examination: 1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed [4]	
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed 🗹	
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹	
TACK-DRY	Hot air convection oven 80°C / 30 minutes	Tack-free to the touch	Passed 🗹	
IMAGING	ORC HMW 680GW - 7 kW 150 mJ / cm <sup>2</sup> Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi	Stouffer 21 step: 12 - 16 (clear on copper)	12	
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 30 sec x 1 cycle Rosin-based flux	No discoloration, peeling, or blistering	Passed 🗸 .	
SOLVENT RESISTANCE (*)	Immersion in PM Acetate 20°C / 30 mins.	No swelling, softening, or blistering	Passed	
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater	1 17	
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed 🗾	

(\*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By:

G.C. Superuison 11/19/21

Name. Title, Date

FRM-0-0181

04/18/12