TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-4000HA).

Mfg. Date: 4 - 29 - 21Warranty Ends: 4 - 29 - 22PSR-4000 GP01EU (DG) Lot # 1042927 **MANUFACTURING TEST METHOD SPECIFICATION** RESULT ps Toki Sangyo RE100U Viscometer Before mixing: Report Only 408 5 rpms @ 25°C After mixing: 220 - 270 ps THIXOTROPIC INDEX Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm After mixing: Report Only FINENESS OF GRIND microns TAI-0-0002 15 microns maximum VISUAL EXAMINATION Microscopic examination: **Passed** 1. 1-mil drawdown of wet film No bubbles, pits, voids, पि particles, color differences. **Passed** 2. Wet film drawdown on No bubbles, pits, voids, ГŦ particles, color differences. grind gauge **SCREENABILITY Passed** দে Visual inspection of screen No surface defects, printed panel such as bubbles, pinholes, etc. पि TACK-DRY Passed Hot air convection oven Tack-free to the touch 80°C / 30 minutes 10 **IMAGING ORC HMW 680GW - 7 kW** Stouffer 21 step: 8 - 12 400 mJ / cm² (clear on copper) Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi **RESISTANCE TO** 260°C (500°F) / 30 sec x 1 cycle **Passed** पि No discoloration, peeling, **SOLDERING (*)** Rosin-based flux or blistering **SOLVENT** Immersion in PM Acetate Passed No swelling, softening, **RESISTANCE (*)** 20°C / 20 mins. or blistering BH PENCIL HARDNESS (*) TAI-0-0020 6H or greater **ADHESION (*)** TAI-0-0021 Passed V 100/100 on copper

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By:

Verified By:

No. C. Supsevisor 5/4/21

Name, Title, Date

FRM-0-0132

3/08/12