TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taivo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-4000DE).

Lot# 9042577 Mfg. Date: 4-25-19 PSR-4000HFX Satin DI Warranty Ends: 1-25-20 **MANUFACTURING SPECIFICATION** RESULT **TEST METHOD PROPERTY** VISCOSITY Toki Sangyo RE100U Viscometer 242 ps 5 rpms @ 25°C After mixing: 220 - 270 ps THIXOTROPIC INDEX Toki Sangvo RE100U Viscometer After mixing: Report Only Viscosity ratio: 5 rpm / 50 rpm microns FINENESS OF GRIND TAI-0-0002 5 microns maximum VISUAL EXAMINATION Microscopic examination: Passed 1. 1-mil drawdown of wet film No bubbles, pits, voids, particles, color differences. **Passed** 2. Wet film drawdown on No bubbles, pits, voids, particles, color differences. grind gauge Passed **SCREENABILITY** Visual inspection of screen No surface defects, printed panel such as bubbles, pinholes, etc. Passed **TACK-DRY** Hot air convection oven Tack-free to the touch 80°C/30 minutes **IMAGING** ORC HMW 680GW - 7 kW Stouffer 21 step: 10 - 14 400 mJ / cm² (clear on copper) Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi **RESISTANCE TO Passed** 260°C (500°F) / 30 sec x 1 cycle No discoloration, peeling, **SOLDERING** (*) Rosin-based flux or blistering **SOLVENT Passed** Immersion in PM Acetate No swelling, softening, **RESISTANCE** (*) 20°C / 20 mins. or blistering PENCIL HARDNESS (*) TAI-0-0020 6H or greater ADHESION (*) **Passed**

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

TAI-0-0021

Verified By	/:				
		SUPER	VISOR	4/26/19	
Name,	Title,		Date		

100/100 on copper