TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with the manufacturing specifications for this product.

S-200Y NP (USA)

Lot# 9092337

Mfg. Date: 9-23-19 Warranty Ends: 3-23-20

ND ONEDHY!		MANUFACTURING	DECKY E
PROPERTY	TEST METHOD	SPECIFICATION	RESULT
VISCOSITY	Toki Sangyo RE100U Viscometer	Before mixing: 290 - 350 ps	2 96 ps
	5 rpms @ 25°C	After mixing: Report Only	473 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	Before mixing: 1.4 - 2.2 After mixing: Report Only	2.0
FINENESS OF GRIND	TAI-0-0002	17.5 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination:		
2.5	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed 🔽
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed 🔽
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹
RESISTANCE TO	260°C (500°F) / 10 sec x 2 cycles	No discoloration, peeling,	Passed
SOLDERING (*)	Rosin-based flux	or blistering	7
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed
RESISTANCE (*)	20^{0} C / 30 mins.	or blistering	
PENCIL HARDNESS (*)	TAI-0-0020	7H or greater	8 H .
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed
(*) - Fin: es @ 140°C (284°F) in a convection oven			

WARRANTY EXTENSION

This product has been retested by the Taiyo America Quality Control department and has been granted a warranty extension.

FRM-0-0083

Warranty period ends:

04/23/20

Authorized By: Luis Marquez QC Supervisor

1/12/12