TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-9000 FXT Matte Black

MANITEACTUDING

Lot # 9050317 Mfg. Date: 5-03-19 Warranty Ends: 2-03-20

		MANUFACTURING	8
PROPERTY	TEST METHOD	SPECIFICATION	RESULT
VISCOSITY	Toki Sangyo RE100U Viscometer	Before mixing: Report Only	191 ps
	5 rpms @ 25°C	After mixing: 140 - 180 ps	151 ps
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination:		
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed 📝
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed
RESISTANCE TO	260°C (500°F) / 10 sec x 1 cycle	No discoloration, peeling,	Passed 🗹
SOLDERING (*)	Rosin-based flux	or blistering	
FLEXIBILITY (*)	TAI-0-0025	No cracking	Passed 🗹
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed 😈

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven.

Verified By: