TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-9000AC).

PSR-9000 FXT White Lot # | | | | 8 27 Mfg. Date: | 1 - 18 - 2 | Warranty Ends: 8 - 18 - 22

		MANUFACTURING		
PROPERTY	TEST METHOD	<u>SPECIFICATION</u>	RESU	ULT
VISCOSITY	Toki Sangyo RE100U Viscometer	Before mixing: Report Only	200	ps
	5 rpms @ 25°C	After mixing: 140 - 180 ps	178	ps
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5	microns
VISUAL EXAMINATION	Microscopic examination:			
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed	। ज
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed	I Ø
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 1 cycle Rosin-based flux	No discoloration, peeling, or blistering	Passed	l Ø
FLEXIBILITY (*)	TAI-0-0025	No cracking	Passed	
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed	। प्

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven.

Verified By:

O.C. Sutsavisor 11/22/21

Name, Title, Date