TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with the manufacturing specifications for this product.

S-200Y NP (USA)	Lot# 9031847	Mfg. Date: 3-18-19 Warranty Ends: 9-18-	-19
	· · · · · · · · · · · · · · · · · · ·	MANUFACTURING	5,
PROPERTY	TEST METHOD	SPECIFICATION	. RESULT
VISCOSITY	Toki Sangyo RE100U Viscometer	Before mixing: 290 - 350 ps	298 ps
	5 rpms @ 25 ⁰ C	After mixing: Report Only	426 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	Before mixing: 1.4 - 2.2 After mixing: Report Only	1.8
FINENESS OF GRIND	TAI-0-0002	17.5 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination:		•
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed 🔽
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed 🔽
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹
RESISTANCE TO	260°C (500°F) / 10 sec x 2 cycles	No discoloration, peeling,	Passed
SOLDERING (*)	Rosin-based flux	or blistering	
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed
RESISTANCE (*)	20°C / 30 mins.	or blistering	
PENCIL HARDNESS (*)	TAI-0-0020	7H or greater	9 H.
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed

(*) - Final cure for these tests was 20 minutes @ 140°C (284°F) in a convection oven

	WARRANTY EXTENSION	V/		e
_	This product has been retested by the Taiyo America Quality	Verified By	Q.C. SUPERVISOR	3/22/19
	Control department and has been granted	Name,	Title,	Date
FRM-0-0083	a warranty extension.		*	1/12/12
	Warranty period ends:			
	12/18/19			

Authorized By:

Luis Marquez QC Supervisor