TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product. This product meets the requirements of IPC-SM-840E Classes FH and FT.

PSR-9000 LDI Amber	Lot#1110237	Mfg. Date: \\l-02-6 Warranty Ends: 5-06	2-22
PROPERTY VISCOSITY THIXOTROPIC INDEX	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: Report Only After mixing: 140 - 200 ps	RESULT 21 ps 158 ps
FINENESS OF GRIND	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm TAI-0-0002	After mixing: Report Only 5 Microns maximum	1.3 5 microns
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 1 cycle Rosin-based flux	No discoloration, peeling,	Passed 🗹
FLEXIBILITY (*)	TA1-0-0025	No cracking	Passed 🗹
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed 🗹

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By:

Title, Date