## TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

## CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with the manufacturing specifications for this product.

S-200Y NP (USA)	Lot# 90.31847	Mfg. Date: 3-18-19 Warranty Ends: 9-18	1 - 19
		MANUFACTURING	<b>V</b>
PROPERTY	TEST METHOD	SPECIFICATION	· <u>RESULT</u>
VISCOSITY	Toki Sangyo RE100U Viscometer	Before mixing: 290 - 350 ps	298 ps
	5 rpms @ 25°C	After mixing: Report Only	426 ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	Before mixing: 1.4 - 2.2 After mixing: Report Only	1.8
FINENESS OF GRIND	TAI-0-0002	17.5 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination:		
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed 🔽
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed 🔽
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 2 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed
SOLVENT RESISTANCE (*)	Immersion in PM Acetate $20^{\circ}\text{C}/30$ mins.	No swelling, softening, or blistering	Passed
PENCIL HARDNESS (*)	TAI-0-0020	7H or greater	9 H
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed
		2	

(\*) - Final cure for these tests was 20 minutes @ 140°C (284°F) in a convection oven

_	WARRANTY EXTENSION This product has been retested by the Taiyo America Quality	Verified By:		3/22/19
1-0-0083	Control department and has been granted a warranty extension.	Name,	Title,	Date 1/12/12
	Warranty period and			

FRM

Warranty period ends: 11/18/19

Authorized By: Luis Marquez QC Supervisor