# SAFETY DATA SHEET

Issuing Date 28-Aug-2015

Revision Date 28-Aug-2015

Revision Number 0

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name PSR-4000 AUS703 140Ps

Other means of identification

SDS NumberMS-00226500-US00SynonymsNone

#### Recommended use of the chemical and restrictions on use

Solder mask part A

Uses advised against No information available

Supplier's details

Manufacturer Address TAIYO INK MFG. CO., Ltd. 900 Hirasawa, Ranzan-machi, Hiki-gun, Saitama, 355-0215 Japan TEL: 81-493-61-2724

#### Emergency telephone number

Emergency Telephone Number

# 2. HAZARDS IDENTIFICATION

#### Classification


This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

81-493-61-2724

Carcinogenicity	Category 2
Flammable liquids	Category 4

#### **GHS Label elements, including precautionary statements**

**Emergency Overview** 



Appearance Green	Physical State Paste.	
	· · · · · · · · · · · · · · · · · · ·	

Odor Mild

#### **Precautionary Statements**

# Prevention

- · Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wear protective gloves/protective clothing/eye protection/face protection.
- · Keep away from flames and hot surfaces No smoking.

#### **General Advice**

• If exposed or concerned: Get medical attention/advice

#### Fire

• In case of fire: Use CO2, dry chemical, or foam to extinguish.

#### Storage

- · Store locked up.
- Store in a well-ventilated place. Keep cool.

#### Disposal

• Dispose of contents/container to an approved waste disposal plant.

#### Hazard Not Otherwise Classified (HNOC)

Not applicable

### Other information

Toxic to aquatic life with long lasting effects

65.7% of the mixture consists of ingredient(s) of unknown toxicity.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %	Trade secret
Barium sulfate	7727-43-7	20-30	*
Dipropylene glycol monomethyl ether	34590-94-8	5-10	*
Talc	14807-96-6	1-5	*
1-Butanone, 2-(dimethylamino)-1-[4-(4-morpholinyl)phenyl]-2-(ph enylmethyl)-	119313-12-1	1-5	*
Naphthalene	91-20-3	1-5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

Description of necessary first-aid measures			
General Advice	If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.		
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.		
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Consult a physician if necessary.		
Inhalation	Move to fresh air. If symptoms persist, call a physician. If breathing is difficult, give oxygen.		

Ingestion	Rinse mouth. Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.	
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.	
Most important symptoms/effects, acute and delayed		
Most Important Symptoms/Effects	No information available.	
Indication of immediate medical attention and special treatment needed, if necessary		

Notes to Physician Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Dry powder. Dry chemical.

Unsuitable Extinguishing Media No information available.

#### Specific Hazards Arising from the Chemical

Combustible liquid. Vapors may travel to source of ignition and flash back. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition.

Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions	Evacuate personnel to safe areas. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Pay attention to flashback. In case of insufficient ventilation wear suitable respiratory equipment.	
Environmental Precautions		
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Collect spillage. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.	
Methods and materials for containment and cleaning up		
Methods for Containment	Prevent further leakage or spillage if safe to do so.	
Methods for Cleaning Up	Dam up. Take up with sand or other noncombustible absorbent material and place into containers for later disposal.	
7. HANDLING AND STORAGE		

#### Precautions for safe handling

Handling	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). In case of insufficient ventilation, wear suitable respiratory equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Keep away from heat, sparks and open flame. No smoking. Do not take internally.
Conditions for safe storage,	including any incompatibilities
Storage	Keep in properly labeled containers. Keep away from heat and sources of ignition. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place.
Incompatible Products	Strong oxidizing agents. Strong acids. Strong bases.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control parameters**

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Barium sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Dipropylene glycol monomethyl ether 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m <sup>3</sup> (vacated) S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> STEL: 150 ppm STEL: 900 mg/m <sup>3</sup>
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 2 mg/m <sup>3</sup>	IDLH: 1000 mg/m <sup>3</sup> containg no asbestos and <1% quartz TWA: 2 mg/m <sup>3</sup>
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m <sup>3</sup> (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m <sup>3</sup>	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures	Showers
	Eyewash stations
	Ventilation systems

#### Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields.
Skin and Body Protection	Lightweight protective clothing. Protective gloves.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

#### **Hygiene Measures**

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical State Odor	Paste. Mild.	Appearance Odor Threshold	Green. No information available.
Property pH Melting Point/Range Boiling Point/Boiling Range Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit lower flammability limit lower flammability limit Vapor Pressure Vapor Density Specific Gravity Water Solubility Solubility in other solvents Partition coefficient: n-octand Autoignition Temperature	Values No data available No data available No data available 81 °C / 177.8 °F No data available No data available	Remarks/ - M None known None known	lethod_
Viscosity Flammable Properties	Combustible material	: may burn but does not ignite re	adily.
Explosive Properties Oxidizing Properties	No data available No data available		
Other information			
VOC Content (%)	29.7		

# **10. STABILITY AND REACTIVITY**

#### **Reactivity**

No data available.

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

Incompatible products. Heat, flames and sparks.

#### Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

#### Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Sulfur oxides.

### **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Product Information	
Inhalation	There is no data available for this product.
Eye Contact	There is no data available for this product.
Skin Contact	There is no data available for this product.
Ingestion	There is no data available for this product.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), heavy aromatic	> 5000 mg/kg (Rat)	>2 mL/kg (Rabbit)	> 590 mg/m³(Rat)4 h
Dipropylene glycol monomethyl ether	= 5230 mg/kg (Rat)	= 9500 mg/kg (Rabbit)	-
Naphthalene	= 1110 mg/kg (Rat) = 490 mg/kg (	= 1120 mg/kg (Rabbit)> 20 g/kg (	> 340 mg/m³ (Rat)1 h
	Rat )	Rabbit )	

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization Mutagenic Effects Carcinogenicity No information available.

No information available. Contains a known or suspected carcinogen. May cause cancer. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Naphthalene	A3	Group 2B	Reasonably Anticipated	Х

ACGIH: (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen

#### IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

### **NTP: (National Toxicity Program)**

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

#### **OSHA: (Occupational Safety & Health Administration)**

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

# Numerical measures of toxicity - Product

Acute Toxicity65.7% of the mixture consists of ingredient(s) of unknown toxicity.The following values are calculated based on chapter 3.1 of the GHS document:LD50 Oral7420 mg/kg; Acute toxicity estimateLD50 Dermal19069 mg/kg; Acute toxicity estimate

# **12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Naphtha (petroleum), heavy aromatic 64742-94-5	EC50 72 h: = 2.5 mg/L (Skeletonema costatum)	LC50 96 h: = 19 mg/L static (Pimephales promelas) LC50 96 h: = 2.34 mg/L (Oncorhynchus mykiss) LC50 96 h: = 1740 mg/L static (Lepomis macrochirus) LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 41 mg/L (Pimephales promelas)		EC50 48 h: = 0.95 mg/L (Daphnia magna)
Dipropylene glycol monomethyl ether 34590-94-8		LC50 96 h: > 10000 mg/L static (Pimephales promelas)		LC50 48 h: = 1919 mg/L (Daphnia magna)
Talc 14807-96-6		LC50 96 h: > 100 g/L semi-static (Brachydanio rerio)		
Naphthalene 91-20-3	EC50 72 h: = 0.4 mg/L (Skeletonema costatum)	LC50 96 h: 5.74 - 6.44 mg/L flow-through (Pimephales promelas) LC50 96 h: = 1.6 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: 0.91 - 2.82 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 1.99 mg/L static (Pimephales promelas) LC50 96 h: = 31.0265 mg/L static (Lepomis macrochirus)		LC50 48 h: = 2.16 mg/L (Daphnia magna) EC50 48 h: = 1.96 mg/L Flow through (Daphnia magna) EC50 48 h: 1.09 - 3.4 mg/L Static (Daphnia magna)

## Persistence and Degradability

No information available.

#### **Bioaccumulation**

Chemical Name	Log Pow
Dipropylene glycol monomethyl ether	-0.064
Naphthalene	3.3

Other Adverse Effects No information available.

# **13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with federal, state, and local regulations

Waste Disposal Methods

Contaminated Packaging

Do not re-use empty containers.

U165

US EPA Waste Number

Chemical Name	RCRA	RC	RA - Basis for Listing	RC	CRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene - 91-20-3	U165 Incl		uded in waste streams:			U165
	F024, F025, F034,		24, F025, F034, F039,			
		K0(	01, K035, K060, K087,			
			K145			
Component	RCRA - Halogena	ted	<b>RCRA - P Series Wast</b>	tes	RCRA - F Series Wastes	RCRA - K Series Wastes
_	Organic Compour	nds				

Naphthalene	Toxic waste
91-20-3 (1-5)	waste number F025
	Waste description:
	Condensed light ends,
	spent filters and filter aids,
	and spent desiccant
	wastes from the production
	of certain chlorinated
	aliphatic hydrocarbons, by
	free radical catalyzed
	processes. These
	chlorinated aliphatic
	hydrocarbons are those
	having carbon chain
	lengths ranging from one
	to and including five, with
	varying amounts and
	positions of chlorine
	substitution.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Naphthalene	Toxic

# **14. TRANSPORT INFORMATION**

Note:According to 49 CRF §173.150(f)(1), this material should be reclassified as NA1993,<br/>Combustible Liquid, NOS if it is shipped in bulk.

DOT

Not regulated

IATA	Not regulated.
IMDG/IMO	Not regulated

# **15. REGULATORY INFORMATION**

International Inventories	
DSL	Does not comply

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Diethylene glycol monoethyl ether acetate	112-15-2	5-10	1.0
Naphthalene	91-20-3	1-5	0.1

# SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene	100 lb	Х	Х	Х

#### <u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Naphthalene	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

#### U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Naphthalene	91-20-3	Carcinogen

#### U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Barium sulfate	Х	Х	Х		
Diethylene glycol monoethyl ether acetate	Х		х	X	
Dipropylene glycol monomethyl ether	Х	X	х	X	Х
Talc	Х	Х	Х		Х
Naphthalene	Х	X	Х	X	

# U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION				
NFPA	Health Hazard 1	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1*	Flammability 2	Physical Hazard 0	Personal Protection X

\*Indicates a chronic health hazard.

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	28-Aug-2015
Revision Date	28-Aug-2015
Revision Note	Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet