SAFETY DATA SHEET

Issuing Date 13-May-2015 Revision Date 11-Jan-2023 Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name UVR-150 G

Other means of identification

Product Code(s) 400250

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use UV Cure Solder Mask

Uses advised against No information available

Supplier's details

Supplier Address

Taiyo America, Inc. 2675 Antler Drive Carson City, NV 89701

TEL: 775-885-9959 (M-F 8-4 PDT)

Email SDSinfo@taiyo-america.com

Emergency telephone number

Emergency Telephone

Number

1-800-255-3924 (USA)

1-813-248-0585 (International)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Acute Oral Toxicity	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Warning

Hazard Statements

Harmful if swallowed

- Causes skin irritation
- Causes serious eye irritation
- May cause an allergic skin reaction

SDS Number: UVR-150G Page 1 / 8



Appearance Green

Physical State Viscous liquid.

Odor Slight Solvent

Precautionary Statements

Prevention

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

• Specific treatment (see supplemental first aid instructions on this label)

Eves

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- Take off contaminated clothing and wash before reuse.
- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation or rash occurs: Get medical advice/attention.

Ingestion

- · Rinse mouth.
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

• None

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Talc	14807-96-6	10-30	*
Trimethylolpropane triacrylate	15625-89-5	10-30	*
2-Hydroxyethyl methacrylate	868-77-9	10-30	*
Silicon dioxide	7631-86-9	1-5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice

Immediate medical attention is required. If symptoms persist, call a physician.

SDS Number: UVR-150G Page 2 / 8

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician. If breathing is irregular or stopped,

administer artificial respiration.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink

plenty of water. If symptoms persist, call a physician.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray. Foam. Dry powder.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Use personal protective equipment. Avoid contact with

skin, eyes and clothing. Keep people away from and upwind of spill/leak.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. Prevent entry into waterways,

sewers, basements or confined areas.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers.

SDS Number: UVR-150G Page 3 / 8

Revision Date 11-Jan-2023 UVR-150 G

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove

and wash contaminated clothing before re-use. Do not breathe vapors or spray mist. Use only in area provided with appropriate exhaust ventilation. Do not eat, drink or smoke when

using this product.

Conditions for safe storage, including any incompatibilities

Keep in properly labeled containers. Keep out of the reach of children. Keep containers Storage

tightly closed in a dry, cool and well-ventilated place.

Incompatible Products Oxidizing agents. Peroxides. Free radical initiators

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH			
Talc	TWA: 2 mg/m ³	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³ containg no			
14807-96-6		-	asbestos and <1% quartz			
			TWA: 2 mg/m ³			
Quartz	TWA: 0.025 mg/m ³ respirable	(vacated) TWA: 0.1 mg/m ³	IDLH: 50 mg/m ³ respirable dust			
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m ³ respirable			
		: (30)/(%SiO2 + 2) mg/m ³ TWA	dust			
		total dust				
		: (250)/(%SiO2 + 5) mppcf				
		TWA respirable fraction				
		: (10)/(%SiO2 + 2) mg/m ³ TWA				
		respirable fraction				
Silicon dioxide	10 mg/m ³	20 mppcf TWA; ((80)/(% SiO2)	IDLH: 3000 mg/m ³			
7631-86-9		mg/m³)	TWA: 6 mg/m ³			

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

> Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and Body Protection Protective gloves. Lightweight protective clothing.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, approved respiratory protection

should be worn.

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area **Hygiene Measures**

> and clothing. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Revision Date 11-Jan-2023 UVR-150 G

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Viscous liquid **Appearance** Green

Odor Slight Solvent **Odor Threshold** No information available

Property Values Remarks/ - Method

No data available None known Hq Melting Point/Range No data available None known **Boiling Point/Boiling Range** No data available None known Flash Point >200 °C / >392 °F None known **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limits in Air

upper flammability limit No data available lower flammability limit No data available

Vapor Pressure No data available None known **Vapor Density** No data available None known **Specific Gravity** No data available None known Water Solubility No data available None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known **Viscosity** No data available None known

Flammable Properties Combustible material: may burn but does not ignite readily.

Explosive Properties No data available **Oxidizing Properties** No data available

Other information

VOC Content (%) 0

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Incompatible products.

Incompatible materials

Oxidizing agents. Peroxides. Free radical initiators

Hazardous decomposition products

SDS Number: UVR-150G Page 5 / 8

Carbon oxides. Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation There is no data available for this product.

Eye Contact Causes serious eye irritation.
Skin Contact Causes skin irritation.
Ingestion Harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Quartz	= 500 mg/kg (Rat)	-	-		
Trimethylolpropane triacrylate	> 5000 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	-		
2-Hydroxyethyl methacrylate	= 5050 mg/kg (Rat)	>3000 mg/kg (Rabbit)	-		
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h		

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization May cause an allergic skin reaction.

Mutagenic Effects No information available.

Carcinogenicity This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of

crystalline silica will not occur from exposure to this product in its current form.

	Chemical Name	ACGIH	IARC	NTP	OSHA
Ī	Silicon dioxide		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic Toxicity Avoid repeated exposure. Repeated contact may cause allergic reactions in very

susceptible persons.

Target Organ Effects Respiratory system. Eyes. Lungs.

Aspiration Hazard No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 1261 mg/kg **LD50 Dermal** 5000 mg/kg mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

SDS Number: UVR-150G Page 6 / 8

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Talc 14807-96-6		LC50 96 h: > 100 g/L semi-static (Brachydanio rerio)		
2-Hydroxyethyl methacrylate 868-77-9		LC50 96 h: 213-242 mg/L flow-through (Pimephales promelas) LC50 96 h: = 227 mg/L (Pimephales promelas)		
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow				
2-Hydroxyethyl methacrylate	0.47				

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Complies
EINECS Complies
ELINCS Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

SDS Number: UVR-150G Page 7 / 8

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65		
Quartz	14808-60-7	Carcinogen		

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Talc	X	X	X		X
Quartz	Х	Х	Х	-	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

1	6	\cap	ГΗ	FR	11	JF	O	RI	M.	Δ-	П	<u></u>	N	ı
	C)_ '					41	•			_		u	ш	

NFPA Health Hazard 2 Flammability 1 Instability 0 Physical and Chemical

Hazards

Health Hazard 2 Flammability 1 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501 13-May-2015

Issuing Date13-May-2015Revision Date11-Jan-2023

Revision Note Updated Contact Information

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet

SDS Number: UVR-150G Page 8 / 8