TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-4000DE).

Mfg. Date: 6-15-21Warranty Ends: 3-15-22Lot#1061587 PSR-4000HFX Satin Black DI **MANUFACTURING RESULT** PROPERTY **TEST METHOD SPECIFICATION** Toki Sangyo RE100U Viscometer 234 ps 5 rpms @ 25°C After mixing: 220 - 270 ps THIXOTROPIC INDEX Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm After mixing: Report Only -5 FINENESS OF GRIND microns TAI-0-0002 5 microns maximum VISUAL EXAMINATION Microscopic examination: **Passed** 1. 1-mil drawdown of wet film No bubbles, pits, voids, LY. particles, color differences. Passed 2. Wet film drawdown on No bubbles, pits, voids, grind gauge particles, color differences. **SCREENABILITY Passed** पि Visual inspection of screen No surface defects. printed panel such as bubbles, pinholes, etc. TACK-DRY Γď Passed Hot air convection oven Tack-free to the touch 80°C/30 minutes \mathbf{H} **IMAGING** ORC HMW 680GW - 7 kW Stouffer 21 step: 10 - 14 500 mJ/cm² (Under Artwork) (clear on copper) Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi RESISTANCE TO 260°C (500°F) / 30 sec x 1 cycle **Passed** No discoloration, peeling, u **SOLDERING (*)** Rosin-based flux or blistering SOLVENT Immersion in PM Acetate No swelling, softening, **Passed RESISTANCE** (*) 20°C / 20 mins. or blistering BH PENCIL HARDNESS (*) TAI-0-0020 6H or greater

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

TAI-0-0021

100/100 on copper

Title. Date

Passed

ADHESION (*)