TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taivo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-4000HA).

Mfg. Date: 12-28-20 Lot # 0122887 PSR-4000 BW01 DI Warranty Ends: 6-28-21 MANUFACTURING **TEST METHOD SPECIFICATION** RESULT **PROPERTY** VISCOSITY Toki Sangyo RE100U Viscometer 5 rpms @ 25°C After mixing: 180 - 220 ps THIXOTROPIC INDEX Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm After mixing: 1.2 - 1.4 FINENESS OF GRIND microns TAI-0-0002 15 microns maximum VISUAL EXAMINATION Microscopic examination: **Passed** 1. 1-mil drawdown of wet film No bubbles, pits, voids, particles, color differences. **Passed** 2. Wet film drawdown on No bubbles, pits, voids, particles, color differences. grind gauge Passed **SCREENABILITY** Visual inspection of screen No surface defects, printed panel such as bubbles, pinholes, etc. **TACK-DRY** Passed Hot air convection oven Tack-free to the touch 80°C / 30 minutes 11 **IMAGING** ORC HMW 680GW - 7 kW Stouffer 21 step: 10 - 14 100 mJ / cm² (clear on copper) Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28- 32 psi **RESISTANCE TO** 260°C (500°F) / 30 sec x 1 cycle **Passed** No discoloration, peeling, **SOLDERING** (*) Rosin-based flux or blistering SOLVENT **Passed** Immersion in PM Acetate No swelling, softening, **RESISTANCE (*)** 20°C / 30 mins. or blistering PENCIL HARDNESS (*) TAI-0-0020 6H or greater **Passed** ADHESION (*) TAI-0-0021 100/100 on copper

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Name,		Title,		Date	
v erineu b		SupERVI.	SOR	12/28/20	
Verified B	×7.				