TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: S-222NA).

S-222NA (402-LV)	Lot # 01110 17	Mfg. Date: 11-10-2- Warranty Ends: 5-10-	-0 21
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: Report Only After mixing: Report Only	RESULT 11,900 cps 20,700 cps
	Brookfield DV-II Viscometer 10 rpms @ RT, spindle #6, 5 mins.	After mixing: 47,000 - 57,000 cps	53,9.00 cps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only	2.4
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5 microns
VISUAL EXAMINATION	Microscopic examination: 1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed 🗾
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed [7]
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed
SOLVENT RESISTANCE (*)	Immersion in PM Acetate 20°C / 30 mins.	No swelling, softening, or blistering	Passed 🔽
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater	814
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed 🕑

(*) - Final cure for these tests was 20 minutes @ 140°C (284°F) in a convection oven

Verified By:		÷ ,
# 4	2.C. SUPERVI	sor 11/13/20
Name,	Title,	Date

FRM-0-0042