TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes FH and FT and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94VTM-0 (File #E166421, UL Name: PSR-9000AN).

PSR-9000 FLX05W2	Lot# 1062347	Mfg. Date: 6-23-21 Warranty Ends: 2-23	-21	
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: 280 - 340 ps After mixing: 200 - 240 ps	RESUI るの	ps
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	Before mixing: 1.00 - 1.40 After mixing: 1.00 - 1.40		29 22
FINENESS OF GRIND	TAI-0-0002	25 microns or less.	5 m	icrons
VISUAL EXAMINATION	Microscopic examination: 1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed	•
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed	ď
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed	
TACK-DRY	Hot air convection oven 80°C/30 minutes	Tack-free to the touch	Passed	J
IMAGING	ORC HMW 680GW - 7 kW 500 mJ / cm ² Horizontal Developer - 1% Na2CO3	Stouffer 21 step: Report Only (clear on copper)	12	
	30°C (86°F) / 60 secs., 28 psi			
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 5 sec x 1 cycle Rosin-based flux	No discoloration, peeling, or blistering	Passed	团
SOLVENT RESISTANCE (*)	Immersion in PM Acetate 20°C / 20 mins.	No swelling, softening, or blistering	Passed	Ø.
PENCIL HARDNESS (*)	TAI-0-0020	H or greater	3 H	
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed	Ø

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven.

Verified/I	By:	
AF.	P.C. JUPERVISOR	6/25/21
Name,		Date

FRM-0-0239