TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: S-222NA).

S-222NA (402-LV)	Lot#1020937	Mfg. Date: $2 - 09 - 2$ Warranty Ends: $8 - 09$	e: 2-09-21 y Ends: 8-09-21		
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: Report Only After mixing: Report Only	<u>RESU</u> 9,500 18,800	cps	
	Brookfield DV-II Viscometer 10 rpms @ RT, spindle #6, 5 mins.	After mixing: 47,000 - 57,000 cps	, 55, 4	00 cps	
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only	3.2		
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5	microns	
VISUAL EXAMINATION	Microscopic examination:				
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed		
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed	V	
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed	Ø	
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed	ď	
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed	P	
RESISTANCE (*)	20°C / 30 mins.	or blistering	8 H		
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater	017	•	
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed		
(*) - Final cure for these tests was 20 minutes @ 140° C (284 F) in a convection oven					

(*) - Final cure for these tests was 20 minutes @ 140 C (284 F) in a convection oven

WARRANTY EXTENSION This product has been Verified By: retested by the Taiyo Title, Date **America Quality** Control department and has been granted a warranty extension. Warranty period ends: 09/09/21

10/14/11

FRM-0-0042

Authorized By:

Luis Marquez

QC Supervisor