## TAIYO AMERICA, INC.

## 2675 Antler Drive, Carson City, NV 89701

Phone: (775) 885-9959 Fax: (775) 885-9972

## CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-4000DE).

Mfg. Date: 1-08-21 Lot# 1010807 PSR-4000HFX Satin Red DI Warranty Ends: 10-08-21 **MANUFACTURING TEST METHOD SPECIFICATION PROPERTY** RESULT Toki Sangyo RE100U Viscometer 257 ps 5 rpms @ 25°C After mixing: 220 - 270 ps THIXOTROPIC INDEX Toki Sangyo RE100U Viscometer 1.7 Viscosity ratio: 5 rpm / 50 rpm After mixing: Report Only FINENESS OF GRIND 5 microns TAI-0-0002 5 microns maximum VISUAL EXAMINATION Microscopic examination: **Passed** 1. 1-mil drawdown of wet film No bubbles, pits, voids, W particles, color differences. **Passed** 2. Wet film drawdown on No bubbles, pits, voids, Tir particles, color differences. grind gauge **SCREENABILITY** Passed W Visual inspection of screen No surface defects. such as bubbles, pinholes, etc. printed panel Passed V TACK-DRY Hot air convection oven Tack-free to the touch 80°C / 30 minutes 13 **IMAGING** Stouffer 21 step: 10 - 14 ORC HMW 680GW - 7 kW 400 mJ / cm<sup>2</sup> (clear on copper) Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 psi RESISTANCE TO Passed 260°C (500°F) / 30 sec x 1 cycle ΓŪ No discoloration, peeling, **SOLDERING** (\*) Rosin-based flux or blistering **SOLVENT** Passed Immersion in PM Acetate No swelling, softening, **RESISTANCE (\*)** 20°C / 20 mins. or blistering SH PENCIL HARDNESS (\*) TA1-0-0020 6H or greater ADHESION (\*) **Passed** TAI-0-0021 100/100 on copper

(\*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

Verified By: Title, Date