

SAFETY DATA SHEET

Issuing Date 13-May-2015

Revision Date 11-Jan-2023

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name PSR-4000 AUS5, PSR-4000 HRS, PSR-4000 CC200HRS Gloss, PSR-4000 CC200HRS Satin

Other means of identification

Product Code(s) 400423, 400422, 800016, 800019

UN-Number UN3082

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solder mask part A

Uses advised against No information available

Supplier's details

Supplier Address

Taiyo America, Inc.
2675 Antler Drive
Carson City, NV 89701
TEL: 775-885-9959 (M-F 8-4 PDT)

Email SDSinfo@taiyo-america.com

Emergency telephone number

Emergency Telephone Number 1-800-255-3924 (USA) 1-813-248-0585 (International)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Flammable liquids	Category 4

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word **Danger**

Hazard Statements

- Suspected of causing cancer
- May damage fertility or the unborn child
- Combustible liquid.



Appearance Green

Physical State Viscous liquid.

Odor Mild Solvent

Precautionary Statements

Prevention

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.

General Advice

- If exposed or concerned: Get medical attention/advice

Fire

- In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep cool.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Toxic to aquatic life with long lasting effects

44.105% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Barium sulfate	7727-43-7	7-13	*
Naphtha (petroleum), heavy aromatic	64742-94-5	10-30	*
Dipropylene glycol monomethyl ether	34590-94-8	1-10	*
Quartz	14808-60-7	1-10	*
1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-	71868-10-5	5-10	*
Talc	14807-96-6	1-5	*
Silicon dioxide	7631-86-9	0-5	*
Propylene glycol monomethyl ether acetate	108-65-6	0-1.5	*
Naphthalene	91-20-3	<1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice

If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Consult a physician if necessary.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If breathing is difficult, give oxygen.
Ingestion	Rinse mouth. Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO₂). Dry powder. Dry chemical.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

Combustible liquid. Vapors may travel to source of ignition and flash back. Risk of ignition In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Use personal protective equipment. In case of insufficient ventilation wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Pay attention to flashback.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information. Collect spillage.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). In case of insufficient ventilation, wear suitable respiratory equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Keep away from heat, sparks and open flame. No smoking. Do not take internally.

Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep away from heat and sources of ignition. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Products Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Barium sulfate 7727-43-7	TWA: 5 mg/m ³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Dipropylene glycol monomethyl ether 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m ³ (vacated) S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	(vacated) TWA: 0.1 mg/m ³ respirable dust : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Talc 14807-96-6	TWA: 2 mg/m ³	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³ containing no asbestos and <1% quartz TWA: 2 mg/m ³
Silicon dioxide 7631-86-9	10 mg/m ³	20 mppcf TWA; ((80)/(% SiO ₂)) mg/m ³	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

Appropriate engineering controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.
Skin and Body Protection Lightweight protective clothing. Impervious gloves.
Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Viscous liquid	Appearance	Green
Odor	Mild Solvent	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	No data available	None known
Flash Point	74 °C	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known
Flammable Properties	Combustible material: may burn but does not ignite readily.	
Explosive Properties	No data available	
Oxidizing Properties	No data available	

Other information

VOC Content (%)	31
VOC (g/l)	382

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Incompatible products. Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Sulfur oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	There is no data available for this product.
Eye Contact	There is no data available for this product.
Skin Contact	There is no data available for this product.
Ingestion	May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), heavy aromatic	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Dipropylene glycol monomethyl ether	= 5230 mg/kg (Rat)	= 9500 mg/kg (Rabbit)	-
Quartz	= 500 mg/kg (Rat)	-	-
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h
Propylene glycol monomethyl ether acetate	= 8532 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	5321 mg/m ³
Naphthalene	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2	Group 1	Known	X
Silicon dioxide		Group 3		
Naphthalene	A3	Group 2B	Reasonably Anticipated	X

ACGIH: (American Conference of Governmental Industrial Hygienists)
 A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
 Group 3 - Not Classifiable as to its Carcinogenicity to Humans
 Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity Contains a known or suspected reproductive toxin. Suspected of damaging fertility or the unborn child.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Target Organ Effects Respiratory system. Eyes. Skin. Central nervous system (CNS).
Aspiration Hazard No information available.

Numerical measures of toxicity - Product

Acute Toxicity 44.105% of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document:
LD50 Oral 2456 mg/kg; Acute toxicity estimate
LD50 Dermal 68486 mg/kg; Acute toxicity estimate
Inhalation
dust/mist 45 mg/L; Acute toxicity estimate
Vapor 179 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Naphtha (petroleum), heavy aromatic 64742-94-5	EC50 72 h: = 2.5 mg/L (Skeletonema costatum)	LC50 96 h: = 19 mg/L static (Pimephales promelas) LC50 96 h: = 2.34 mg/L (Oncorhynchus mykiss) LC50 96 h: = 1740 mg/L static (Lepomis macrochirus) LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 41 mg/L (Pimephales promelas)		EC50 48 h: = 0.95 mg/L (Daphnia magna)
Dipropylene glycol monomethyl ether 34590-94-8		LC50 96 h: > 10000 mg/L static (Pimephales promelas)		LC50 48 h: = 1919 mg/L (Daphnia magna)
Talc 14807-96-6		LC50 96 h: > 100 g/L semi-static (Brachydanio rerio)		
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

Naphthalene 91-20-3	EC50 72 h: = 0.4 mg/L (Skeletonema costatum)	LC50 96 h: 5.74 - 6.44 mg/L flow-through (Pimephales promelas) LC50 96 h: = 1.6 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: 0.91 - 2.82 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 1.99 mg/L static (Pimephales promelas) LC50 96 h: = 31.0265 mg/L static (Lepomis macrochirus)	LC50 48 h: = 2.16 mg/L (Daphnia magna) EC50 48 h: = 1.96 mg/L Flow through (Daphnia magna) EC50 48 h: 1.09 - 3.4 mg/L Static (Daphnia magna)
------------------------	---	--	---

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Naphtha (petroleum), heavy aromatic	2.9 - 6.1
Dipropylene glycol monomethyl ether	-0.064
Propylene glycol monomethyl ether acetate	0.43
Naphthalene	3.3

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene - 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165
Xylene - 1330-20-7		Included in waste stream: F039		U239
Component	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3 (<1)			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

14. TRANSPORT INFORMATION

Note: Not regulated in quantities less than 5 liter per individual container. See IATA SP A197, IMDG 2.10.2.7 and ADR SP 375.

DOT

UN-Number UN3082
Proper shipping name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphthalene), 9, III, Marine Pollutant, Poison-Inhalation Hazard, Zone B, Poison
Emergency Response Guide Number 171

UN-Number UN3082
Proper Shipping Name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphthalene), 9, III, Marine Pollutant

UN-Number UN3082
Proper Shipping Name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphthalene), 9, III

UN-Number UN3082
Proper shipping name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphtha (petroleum), heavy aromatic), 9, III

IATA

UN-Number UN3082
Proper Shipping Name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
ERG Code 9L
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphtha (petroleum), heavy aromatic), 9, III

UN-Number UN3082
Proper Shipping Name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
EmS No. F-A, S-F
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphtha (petroleum), heavy aromatic), 9, III, Marine Pollutant

UN-Number UN3082
Proper Shipping Name Environmentally hazardous substance, liquid, n.o.s.
Hazard Class 9
Packing Group III
Classification Code M6
Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphtha (petroleum), heavy aromatic), 9, III

UN-Number	UN3082
Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s.
Hazard Class	9
Packing Group	III
Classification Code	M6
Tunnel Restriction Code	(E)
Description	UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphtha (petroleum), heavy aromatic), 9, III, (E)
Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s.
Hazard Class	9
Packing Group	III
Classification Code	M6
Special Provisions	274, 335, 601
Description	UN3082, Environmentally hazardous substance, liquid, n.o.s. (1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-, Naphthalene), 9, III
Limited Quantity	5 L

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
EINECS	Complies
ELINCS	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Diethylene glycol monoethyl ether acetate	112-15-2	10-30	1.0
Naphthalene	91-20-3	<1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ

Naphthalene	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ
-------------	--------	---

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen
Naphthalene	91-20-3	Carcinogen
Titanium dioxide	13463-67-7	Carcinogen
Ethylbenzene	100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Barium sulfate	X	X	X		
Dipropylene glycol monomethyl ether	X	X	X	X	X
Quartz	X	X	X	-	X
Talc	X	X	X		X
Silicon dioxide	X	X	X		
Melamine	X	X	X		
Naphthalene	X	X	X	X	
1,2,4 Trimethylbenzene	X	X	X	X	X
Silica gel		X	X		
Xylenes (o-, m-, p- isomers)	X	X	X	X	X
Titanium dioxide	X	X	X	-	X
n-Butyl acetate	X	X	X		X
Diisobutyl ketone	X	X	X		X
2-Phenoxyethanol	X		X	X	
Ethylbenzene	X	X	X	X	X
Isobutyl alcohol	X	X	X		X
Isopropyl alcohol	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 1	Flammability 2	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 1*	Flammability 2	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 13-May-2015
Revision Date 11-Jan-2022
Revision Note Updated Contact Information

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet